

[Switch](#) > [Campus Switch](#) > SW43-49R-2PS-1D-2SF-2Y

SW43-49R-2PS-1D-2SF-2Y



SW43-49R-2PS-1D-2SF-2Y

Product Features

[Intelligent stacking technology](#)

SW43-49R-2PS-1D-2SF-2Y switch is equipped with Maipu VST stacking function that allows a minimum of two devices to be stacked into one logical device. The 10G SFP+ ports. VST (Virtual Switching Technology) stacking combines multiple switches to form a logical virtual switch, improving device and link reliability, simplifying network expansion, and simplifying configuration and management.

[High availability](#)

SW43-49R-2PS-1D-2SF-2Y switch offers advanced redundancy and reliability features, catering to diverse networking requirements. In addition to supporting traditional spanning tree protocols such as STP, RSTP, and MSTP, the switch also complies with the ITU-T G.8032 international standard. This Ethernet Protection Switching (ERPS) protocol enables rapid 50ms failover within Ethernet ring network topologies, ensuring seamless connectivity and minimal downtime.

[Perfect security policy](#)

SW43-49R-2PS-1D-2SF-2Y switch offers a comprehensive suite of security features, including user authentication, port security, ACLs, loopback detection, 802.1X authentication. It also incorporates IP Source Guard, DHCP/ND Snooping, Host Guard, Dynamic ARP Inspection, and PPPoE+ security mechanisms. These robust security functions ensure user access and network protection.

Additionally, the switch supports MAC+IP+VLAN binding, 802.1X authentication, and countermeasures against network storm, DOS/DDOS, ARP, and protocol packet attacks. This makes the SW43-49R-2PS-1D-2SF-2Y switch ideal for large-scale, multi-service, and complex-traffic networks.

[Advanced QoS](#)

SW43-49R-2PS-1D-2SF-2Y switch offers sophisticated QoS capabilities for optimal network performance. Supporting eight queues per port and advanced scheduling algorithms such as SP, RR, WRR, and WDRR, the switch effectively manages traffic prioritization and resource allocation. The switch accommodates diverse priority mapping techniques, including 802.1p, CoS, and DSCP, enabling fine-grained control over traffic classification and prioritization. With granular port traffic rate limiting and time-based controls, network administrators can regulate bandwidth usage as needed. To optimize network performance and minimize congestion, SW43-49R-2PS-1D-2SF-2Y switch employs advanced congestion management techniques, such as Tail Drop and RED packet loss algorithms. These mechanisms help maintain seamless network operation while ensuring efficient delivery of critical data.



Product Specifications

Hardware specifications	
Physical ports	48*100/1000M Base-T interfaces, 4*10G SFP+ interfaces, PoE Enable, One Extension Slot, Dual Power Slots.
Management interface	One Console port, one USB interface
Switching capability (bps)	216Gbps
Power	Input voltage (AC): 100V ~ 240V, 50Hz ~ 60Hz
Temperature	Work temperature: -5°C to 50°C Storage temperature: -40°C to 70°C
Humidity	Work humidity: 10% to 90%, no-condensing Storage humidity: 5% to 95%, no-condensing
Dimension (W×D×H)	442mm×420mm×44.2mm

Open

▼

Order Information

Product model	Description
Access switch	48*100/1000M Base-T interfaces, 4*10G SFP+ interfaces, One Extension Slot, PoE Enable, Dual Power Slots.
Power module	AC PoE Power Supply Module, 500W, AC input 100-240V x2
DAC stacking cable	SFP+ DAC stacking cable, SFP+ to SFP+, 10Gbps 1.5 meters length x1
Optical module	10G SFP+ 1310nm 10-20km LC DDM Single-mode x2
Support	Next-business-day parts' delivery, remote support 24 hours a day, 7 days a week, for 2 Years

Close

▲

			Home	Product	Solution	Support	Partner	News&Case	About Maipu	中	Q
Service Products	Video	Milestone									
Warranty Policy			Contact Us								
Technical Training System											